Poliermotor PM 30N

Polishmotor PM 30N

Poliermotor einsetzbar in Praxis und Labor. 2-stufig regelbar:1400 U/min bzw. 2800 U/min. Die Oberfläche besteht aus Aluminiumguss.
Freistehender Poliermotor der auch in Poliereinheit eingesetzt werden kann.
Einfaches montieren der Polierspindel möglich.
Verfügt über einen Sicherheitsschalter.
Durch die vorbereiteten Bohrlöcher ist eine Fixierung direkt an der Werkbank möglich.

Geschwindigkeit	Spannung	Leistung	Maße	Gewicht
1400/2800 U/min	220-240 V	400 W	380x200x260 mm	10 Kg

Polishmotor installing in the practice and in the laboratory. 2-steps adjustable: 1400 U/min. or 2800 U/min.
The surface ist made of aluminium founding. Exposed polishmotor, which although could put into the polishunit. Simply fitting of the polishspindle is possible.
Safetyswitch is available. Through the prepared drill-holes is a fixing directly at the bench possible.

Tecnical data

speed	voltage	power	dimension	weight
1400/2800 rpm	220 V - 240 V	400 W	380x200x260 mm	10 Kg

Dati Tecnici

Velocitá Rpm	Voltaggio	Potenza	Dimensioni	Peso
1400/2800 rpm	220 V - 240 V	400 W	380x200x260 mm	10 Kg